


UPPAbaby®
ARIA™ V2



From 4-30 lbs



Product Information	2	Base Installation With Lower Anchors	28
Registration	2	Leveling Base	28
Certification	2	Attaching the Lower Anchors	29
Child Use Recommendations	3	Installing Load Leg	30
Start Here	4	What is a Waterfall?	31
The Right Fit	5	Safety Check	32
Notice of Expiration	6	Uninstalling Base	34
		Storing Load Leg	35
Warnings and General Safety Instructions	7		
Features Overview	16	Base Installation With Vehicle Seat Belt	36
Overview of Base	16	Leveling Base	36
Overview of Carrier	18	Lap/Shoulder Routing Method	38
Overview of All-Weather Footcover	20	Lap Belt Only Routing Method	40
		Installing Load Leg	42
Vehicle Compatibility	22	What is a Waterfall?	43
Choosing A Vehicle Seating Location	22	Safety Check	44
Determining Best Installation Method	23	Uninstalling Base and Storing Load Leg	46
LATCH (Lower Anchors and Tethers for Children)	24		
Overview of Vehicle Seat Belt Systems	25		
Unsafe Vehicle Seat Belt Systems and Seating	26		

Carrier Installation with Vehicle Seat Belt	47	Stroller Compatibility	67
Installation Method	47	Fitting Carrier to Stroller Frame	67
Leveling the Carrier	48	Releasing Carrier from Stroller Frame	68
Lap/Shoulder Belt EU Routing Method	49		
Aircraft Installation Method	52	Care and Maintenance	69
Safety Check	55	SIP Padding Removal	69
		Seat Padding Removal	70
General Use	56	Seat Padding Installation	72
Infant Insert	56	SIP Padding Installation	74
SIP Carriage and Harness Positioning	59	Cleaning	75
Securing Your Child	60		
Attaching Carrier to Base	62	Warranty	76
Removing Carrier from Base	63		
Using Canopy	64		
Using Carry Handle	65		
Safety Check	66		

**Read all instructions before use
of this Child Restraint.**

Keep these instructions for future reference.

Product Information

REGISTRATION

Model Number: _____

Manufactured Date: _____

Expiration Date: _____

TAKE A MOMENT TO FILL OUT THE ABOVE INFORMATION.

Information can be found on the manufacture labels or engraved on the underside of the carrier.



Child restraints could be recalled for safety reasons. You must register this restraint to be reached in a recall. Send your name, address, email address if available and the restraint's model number and manufacturing date to 276 Weymouth Street, Rockland, MA 02370 or call (844) 823-3132 or register online at: uppababy.com/register/carseat. For recall information, call the U.S. Government's Vehicle Safety Hotline at 1-888-327-4236 (TTY: 1-800-424-9153), or go to <http://www.NHTSA.gov>

CERTIFICATION



This Child Restraint system conforms to all applicable Federal Motor Vehicle Safety Standards (FMVSS).



This Child Restraint is certified for aircraft use. UPPAbaby and the Federal Aviation Administration (FAA) strongly urge you to secure your child in a Child Restraint system (CRS) or device for the duration of your flight.

Product Information

CHILD USE RECOMMENDATIONS

Children should remain rear-facing for as long as possible.

UPPAbaby advises that all infants and toddlers should ride in a rear-facing car safety seat (CSS) as long as possible, until they reach the highest weight or height allowed by their CSS's manufacturer. This child restraint is for use by children who meet BOTH requirements below:

WEIGHT REQUIREMENTS: 4 – 30 lbs (1.8 – 13.6 kg)

HEIGHT REQUIREMENTS: 30 in (76.2 cm) or less

Product Information – Start Here


Size Requirements



From 4 – 30 lbs
(1.8 – 13.6 kg)
and 30 in (76.2 cm) or less

Attach Carrier to Base

Place carrier on base until a click is heard.




Check for a secure connection by pulling up on carry handle.

Comfort Inlay Usage

Back Positioning Insert

Remove Back Positioning Insert when the child reaches approximately **4 Months**.




Preemie Cushion

Remove Preemie Cushion once infant reaches approximately **9 lbs (4.1 kg)**.



Product Information – The Right Fit

Headrest/Harness Placement


Loosen harness




Pull up on adjuster tab and slide the head restraint up or down



The top of the child's head should not be less than 1" (2.5 cm) from the top of the headrest structure.



Minimum 1" (2.5 cm) gap between the child's head and top of headrest **A**. Harness should be at the shoulders or 1-2 positions below **B**.




Retainer clip must be at armpit **A** level and harness straps should be snug **B**.

Product Information

NOTICE OF EXPIRATION

Discontinue use of this child restraint after 7 years from the date of manufacture or after a crash. Refer to labels on bottom of Carrier and Base.



WARNING

DEATH OR SERIOUS INJURY CAN OCCUR

According to accident statistics, children are statistically safer when properly restrained in the rear seating positions than in the front seating positions, whether there are airbags, advanced airbags or no airbags at all. To ensure your child's safety refer to approved seating positions on page 20 in this manual or your Vehicle's Owner Manual.

NEVER leave Child Restraint unsecured in your vehicle even when it is unoccupied. In a crash, it could become a projectile and injure other vehicle occupants. Use only in rear-facing position when using it in the vehicle

Warnings and General Safety Information




NEVER place this child restraint on a front seat with an airbag. **DEATH OR SERIOUS INJURY** can occur. An airbag can strike a rear-facing infant restraint with enough force to crack the shell and seriously injure or kill an infant. The back seat is the safest place for children 12 and under. Refer to the vehicle owner's instruction book before installing this child restraint in a seating position with side airbags.

Snugly adjust the belts provided with this child restraint around your child. A snug strap should not allow any slack. It lies in a relatively straight line without sagging. It does not press on the child's flesh or push the child's body into an unnatural position.

Warnings and General Safety Information

WARNING



Children have STRANGLED in loose or partially buckled harness straps. Fully restrain the child even when carrier is used outside the vehicle.

SUFFOCATION HAZARD: Infant carrier can roll over on soft surfaces and suffocate child. **NEVER** place carrier on beds, sofas, or other soft surfaces.

- **NEVER** leave child in carrier when straps are loose or undone.
- **NEVER** place carrier near a window where cords from blinds or drapes could strangle a child.

Warnings and General Safety Information

- **NEVER** hang strings on or over the carrier or attach to handle.
- **NEVER** place items with a string around a child's neck, such as hood strings, pacifier cords, etc.

FALL HAZARD: Child's movement can slide carrier.

- **NEVER** place carrier on counter tops, tables, or other elevated surfaces.
DO NOT use on shopping carts.
- **NEVER** leave child unattended.

Warnings and General Safety Information

WARNING



FALL HAZARD: The carrier can fall from the shopping cart.
DO NOT USE on shopping cart.

SAFETY WARNINGS

Failure to follow these instructions could result in serious injury to your child or other vehicle occupants.

- **ALWAYS** keep child properly harnessed when child is in seat.
- **DO NOT** remove or cover up any of the warning or product labels on this Child Restraint. All labels include information required by law.

Warnings and General Safety Information

- **DO NOT** lubricate buckles and fasteners.
- **ALWAYS** check all surfaces of restraint before securing your child. In warm weather, Child Restraints can become very hot. Park in the shade or where sun does not directly hit the child restraint. Cover the Child Restraint with a sheet or blanket when not in use.
- **ALWAYS** properly store lower anchor connectors when not in use.
- Check the vehicle owner's manual for more information about airbag/child restraint use.
- **DO NOT** use seat if it is damaged or broken, expired (over 7 years from date of manufacture), missing instructions, missing parts, or if the straps are cut, frayed, or damaged in any way.
- **DO NOT** use this child restraint system if it has been in a vehicle accident.

Warnings and General Safety Information


- **DO NOT** use clothing or blankets that interfere with fastening or tightening the harness **INSTEAD** place a blanket over the child after being properly secured in the harness.
- **DO NOT** use this child restraint system if the top of the child's head is less than 1" from the top of the headrest when in its highest position.
- **DO NOT** use this Child Restraint system in a vehicle seating position where it cannot be tightly secured.
- **DO NOT** install in rear-facing and side-facing vehicle seats.
- **DO NOT** modify this restraint except as instructed in this instruction book. Minor modifications can change the way a Child Restraint performs in a crash.
- **DO NOT** leave loose objects, e.g. cups, toys, bags, umbrellas, etc., in the vehicle because they can become deadly projectiles in a crash.

Warnings and General Safety Information


- **DO NOT** take child out of the Child Restraint while the vehicle is moving.
- **DO NOT** allow children to play with this Child Restraint. It is not a toy.
- **DO NOT** use any accessories, pads, or products supplied by other manufacturers with this Child Restraint, unless approved and tested by UPPAbaby. Items not tested with this restraint could injure your child.
- **DO NOT** use a child restraint with damaged or missing parts.
- **DO NOT** place carrier on top of shopping cart. Carrier will not be secure and could fall causing injury to child.
- **DO NOT** hang objects from Rear Vehicle Seat Belt Guide.
- **DO NOT** carry by the canopy.
- Properly store lower anchor connectors when not in use.

Features Overview – Overview of Base

- 1 Vehicle Belt Path (2)
- 2 Lower Anchor Connector Release Buttons (2)
- 3 Anti-Rebound+ Panel
- 4 Tightness Indicator
- 5 Lower Anchor Connectors
- 6 Lower Anchor Connector Webbing
- 7 Vehicle Belt Lock-Off (Closed)
- 8 Level Adjust Handle
- 9 Vehicle Belt Lock-Off (Open)
- 10 Load Leg Angle Indicator
- 11 Load Leg Extension Release Button
- 12 Level Angle Indicators (2)
- 13 Level Adjustment Foot
- 14 Lower Anchor Connector Storage
- 15 Load Leg Release Button




Features Overview – Overview of Base





Features Overview – Overview of Carrier

- 1 Side Impact Protection (SIP)
- 2 Harness Covers (2)
- 3 Buckle
- 4 Infant Insert
- 5 Harness Adjuster Release
- 6 Harness Adjuster Strap
- 7 Buckle Latch Plates (2)
- 8 Vehicle Seat Belt Guides (2)
- 9 Retainer Clip
- 10 Harness Straps
- 11 Instruction manual location
- 12 Canopy
- 13 (SIP) Adjustment Tab
- 14 Carrier Release From Base/Stroller
- 15 Carry Handle Adjustment Buttons (2)
- 16 Stroller Attachment
- 17 European Vehicle Belt Guide



Features Overview – Overview of Carrier



General Usage – All-Weather Footcover


ATTACHING THE FOOTCOVER

NOTE: The footcover can only be used on stroller and not in vehicle.


- 1 Loop the elastic bands over the belt guide slots to ensure a secure fit.
- 2 Secure footcover over front of the carrier and tuck the front edge underneath the carrier.
- 3 Route the harness adjuster strap through the alok button on the footcover.
- 4 The footcover can be used in two positions: fully extended or partially folded.
- 5 Footcover can be adjusted by folding back the top and fastening the magnetic buttons together.

NOTE: To remove footcover follow steps in reverse.

⚠️ USE ONLY on stroller.
⚠️ DO NOT use in vehicle.



General Usage – All-Weather Footcover




Vehicle Compatibility – Choosing a Vehicle Seating Location

Please read the following information before installing this Child Restraint!

The safest seating position is one that works best for your specific car seat, family and vehicle. When determining whether the Aria rear-facing car seat can be used with lower anchors in the rear center seating position, it is critical that you refer to your vehicle owner's instruction book. If the Aria does not install best in the rear center seating position, it is recommended to move to one of the outboard seating positions.

Before installing this child restraint you **MUST** determine the method of installation and the best vehicle seating position for that method. This child restraint can be installed either using **LATCH** or the **VEHICLE SEAT BELT**.




Vehicle Compatibility – Determining Best Installation Method


At this point take out your VEHICLE OWNER'S INSTRUCTION MANUAL. You will need this to look up different features in your vehicle that might affect the installation.

WARNING: NEVER place a rear-facing only child restraint in front of an active airbag.


BASE INSTALLATION



Lower Anchor
(page 26)



Lap/Shoulder Belt
(page 34)



Lap Belt Only (page 34)

CARRIER INSTALLATION



**Lap/Shoulder Belt
EU Routing**
(page 44)



NOTE: Mandatory carry handle use positions, must be in either the (5th) rebound position or (4th) carry position when the car seat is in the vehicle.




Vehicle Compatibility

LATCH (Lower Anchors and Tethers for Children)

Most vehicles manufactured after September 1, 2002 are equipped with **LATCH (Lower Anchors and Tethers for Children)**. Check your vehicle owner's instruction book to determine lower anchor compatible seating positions.

NOTE: No tether is required with this rear-facing carrier. Only lower anchors are used.

NOTE: In order to use the rear center seating position with lower anchor, the distance between the lower anchors may be up to 22" (55.9 cm) and the seating position must be approved by the vehicle manufacturer. If spacing between the lower anchors is greater than 22" (55.9 cm) or if the seating position is not approved by the vehicle manufacturer then use the vehicle seat belt for installation.



Vehicle Compatibility

Overview of Vehicle Seat Belt Systems




If you do not use lower anchor to properly secure the child restraint you must use the **VEHICLE SEAT BELT SYSTEM**. Seat belt systems vary by make, model, and year of [your vehicle]. There are some vehicle belts that will NOT work with this child restraint or that require additional steps.


CHECK YOUR VEHICLE OWNER'S INSTRUCTION MANUAL for information regarding your vehicle seat belt system(s).

This child restraint is compatible with most vehicle seat belt systems.

VEHICLE SEAT (LAP/SHOULDER BELT)



VEHICLE SEAT (LAP BELT ONLY)



SLIDING LATCH PLATE




SEWN-ON LATCH PLATE



LOCKING LATCH PLATE




LOCKING LATCH PLATE




Vehicle Compatibility – Unsafe Vehicle Seat Belt Systems and Seating

This Child Restraint can only be installed on vehicle seats that face forward.

DO NOT install in seats that face to the sides or rear of the vehicle.




ALWAYS park on a level surface when installing a Child Restraint.




Vehicle Compatibility – Unsafe Vehicle Seat Belt Systems and Seating


DO NOT use this Child Restraint with the following seat belt systems:




Lap belts with
emergency locking
retractor




Motorized (automatic)



Lap/Shoulder with
two retractors



Door mounted



Inflatable

WARNING! DEATH OR SERIOUS INJURY CAN OCCUR.
CHECK YOUR Vehicle instruction book for information regarding your vehicle seat belt system(s). Not all vehicle seat belts work with this Child Restraint.



Base Installation with Lower Anchors

We recommend using the load leg to optimize safety of the child in the seat. Load leg should be placed in stowed position when not in use. If installing without the load leg, bypass step 1 and proceed to step 2.

LEVELING BASE


- 1 Press the load leg release button on bottom of the base and pull load leg out from storage. Place on the vehicle seat with the load leg extended toward the front of the vehicle cushion.

NOTE: We recommend removing the vehicle floor mat before installation.

- 2 Lift the level adjust handle on the top of the base to extend the foot and change the recline angle. Check the bubble level angle indicator on either side of the base. The base is level when the bubble is fully between the lines. NO partial bubble allowed.




NOTE: If the bubble is not visible, lower the foot to the lowest position and complete installation. Upon completion, the bubble should fall between the two lines.

NOTE: Vehicle must be parked on a level surface to properly level the base.



If proper angle cannot be achieved with level adjustable foot, a rolled towel may be used. Foot must be in fully extended position.

Base Installation with Lower Anchors



ATTACHING THE LOWER ANCHORS

- 1 Locate the lower anchor connectors on either side of the base and remove by pushing the corresponding orange button while pulling the connector out of the lower anchor storage pocket.

- 2 Attach the lower anchor connectors to the vehicle lower anchors located in the vehicle seat bight (crease of seat).

NOTE: Check lower anchor connectors are in the upright position.

- 3 Apply pressure firmly into the base allowing excess lower anchor connector webbing to retract and tighten.

NOTE: A rocking motion may be necessary to retract excess lower anchor connector webbing.

NOTE: Anti-Rebound+ Panel must make full contact with the seat back. If it does not make full contact, please refer to the Waterfall note (page 29).



Installation is complete when tightness indicator turns from **RED** to **GREEN** and stays **GREEN** when downward push is discontinued.



Base Installation with Lower Anchors

CONTINUE IF USING PREFERRED LOAD LEG INSTALLATION





INSTALLING LOAD LEG

- 1 After the base is secured, rotate load leg extension until its showing fully **GREEN**.
- 2 Using two hands, separate the two ends ensuring the bottom of the load leg foot is making good contact with the vehicle floor.




NOTE: After installing the load leg, check the level angle indicator on base to ensure the bubble is still within the lines.



REVIEW SAFETY CHECK ON PAGE 30.


All steps must be achieved.

Base Installation with Lower Anchors



WHAT IS A WATERFALL?

Many late model vehicles have what industry professionals call a waterfall. A waterfall is the wedge of material where your vehicle seat cushion and seat back meet. In some cases, this may prevent the Anti-Rebound+ Panel from making full contact with the vehicle seat back.




This is an easy issue to resolve by following the steps below:

- 1 Uninstall your Aria base.
- 2 Adjust the level adjustment foot to achieve proper recline level.
- 3 Push the base into the seat back. If there is a gap between the top of the Aria base and the back of the vehicle seat, place a rolled hand towel in the gap flush with the top of the base.
- 4 Proceed to **BASE INSTALLATION WITH LOWER ANCHORS** (page 26). Follow Safety Check (page 30) to confirm proper installation.



Base Installation with Lower Anchors – Safety Check



Base doesn't move more than 1" (2.5 cm) side-to-side and front-to-back at the belt path.
Lower anchor connector webbing is secure and untwisted.




Ensure tightness indicator is **GREEN** after each use. If it is not, apply pressure by pushing base into seat bight (crease of seat) to tighten.

Base Installation with Lower Anchors – Safety Check



Recline angle is correct. Check the level angle indicator on base to ensure the bubble is still within the lines. NO partial bubble allowed.



ALWAYS check the Recline Position Indicator on the base and adjust the recline bubble to be between the designated range indicated for the infant insert use.





Make sure the load leg is secured and contacts the vehicle floor. Check that the load leg angle indicator is **GREEN**. Ensure good contact between load leg foot and floor. Always store the load leg under the base when not in use.

ALL STEPS MUST BE COMPLETE.

If not, return to page 26 and start over.





Base Installation with Lower Anchors



UNINSTALLING BASE

- 1 Press the **RED** button on the lower anchor connector while pulling the connector off the vehicle anchor.
- 2 Store lower anchor connectors in designated housing found on each side of the base.

Base Installation with Lower Anchors



STORING LOAD LEG

- 1 Push load leg extension release button on back of load leg and bring foot up until it locks into place.
- 2 Bring load leg back into base until it clicks into secure/stowed position.



Base Installation with Vehicle Seat Belt

We recommend using the load leg to optimize safety of the child in the seat. Load leg should be placed in stowed position when not in use. If installing without the load leg, bypass step 1 and proceed to step 2.

LEVELING BASE

- 1 Press the load leg release button on bottom of the base and pull load leg out from storage. Place on the vehicle seat with the load leg extended toward the front of the vehicle cushion.


NOTE: We recommend removing the vehicle floor mat before installation.

- 2 Lift the level adjust handle on the top of the base to extend the foot and change the recline angle. Check the bubble level angle indicator on either side of the base. The base is level when the bubble is fully between the lines. NO partial bubble allowed.

NOTE: If the bubble is not visible, lower the foot to the lowest position and complete installation. Upon completion, the bubble should fall between the two lines.

NOTE: Vehicle must be parked on a level surface to properly level the base.


- 3 Open the lock-off door by lifting the top then the bottom portions to access the belt path.



Base Installation with Vehicle Seat Belt



3



If proper angle cannot be achieved with level adjustable foot, a rolled towel may be used. Foot must be in fully extended position.



Proceed to chosen installation method:

LAP/SHOULDER ROUTING METHOD Page 36

LAP BELT ONLY ROUTING METHOD Page 38




Base Installation with Vehicle Seat Belt Lap/Shoulder Routing Method




- 1 Route the vehicle belt through the vehicle belt path while guiding the lap portion of the belt as close as possible to the top of the lock-off where the door hinges. Buckle the vehicle belt.
- 2 Hold shoulder portion of belt above base. With one hand, push down in the direction of the seat bight (crease of seat) and hold firm as you pull shoulder belt.

Base Installation with Vehicle Seat Belt Lap/Shoulder Routing Method




- 3 While holding the shoulder belt firmly, check the indicator. If **GREEN**, close the top of the lock-off over the lap/shoulder belt.

NOTE: Tightness indicator should be **GREEN**.



- 4 Push the bottom of the lock-off all the way down until you hear an audible click.

NOTE: Anti-Rebound+ Panel must make full contact with the seat back. If it does not make full contact, refer to the Waterfall note (page 41).



LOAD LEG INSTALLATION CONTINUE TO PAGE 40.

REVIEW SAFETY CHECK ON PAGE 42.

All steps must be achieved.





Base Installation with Vehicle Seat Belt

Lap Belt Only Routing Method


- 1 Route the vehicle belt through the belt path while guiding the lap portion of the belt as close as possible to the topside of the lock-off where the door hinges. Buckle the vehicle
- 2 With one hand push down base and hold firm as you pull lap belt to tighten and remove any slack.

NOTE: Tightness indicator should be **GREEN**.




Base Installation with Vehicle Seat Belt

Lap Belt Only Routing Method




- 3 While holding the excess lap belt webbing, firmly check the indicator. If **GREEN**, close the top of the lock-off over the vehicle belt.

NOTE: Tightness indicator should be **GREEN**.



- 4 Push the bottom of the lock-off all the way down until you hear an audible click.

NOTE: Anti-Rebound+ Panel must make full contact with the seat back. If it does not make full contact, please refer to the Waterfall note (page 41).



LOAD LEG INSTALLATION CONTINUE TO PAGE 40.

REVIEW SAFETY CHECK ON PAGE 42.

All steps must be achieved.



Base Installation with Vehicle Seat Belt

CONTINUE IF USING PREFERRED LOAD LEG INSTALLATION





INSTALLING LOAD LEG

- 1 After the base is secured, rotate load leg extension until its showing fully **GREEN**.
- 2 Using two hands, separate the two ends ensuring the bottom of the load leg foot is making good contact with the vehicle floor.




NOTE: After installing the load leg, check the level angle indicator on base to ensure the bubble is still within the lines.



REVIEW SAFETY CHECK ON PAGE 42.


All steps must be achieved.

Base Installation with Vehicle Seat Belt



WHAT IS A WATERFALL?

Many late model vehicles have what industry professionals call a waterfall. A waterfall is the wedge of material where your vehicle seat cushion and seat back meet. In some cases, this may prevent the Anti-Rebound+ Panel from making full contact with the vehicle seat back.




This is an easy issue to resolve by following the steps below:

- 1 Uninstall your Aria base.
- 2 Adjust the level adjustment foot to achieve proper recline level.
- 3 Push the base into the seat back. If there is a gap between the top of the Aria base and the back of the vehicle seat, place a rolled hand towel in the gap flush with the top of the base.
- 4 Proceed to **BASE INSTALLATION WITH VEHICLE SEAT BELT** (page 36 or 38) based on your method of installation). Follow Safety Check (page 42) to confirm proper installation.




Base Installation with Vehicle Seat Belt Safety Check



Lock-off must be used at all times when installing with a vehicle seat belt.

Vehicle Belt is secure and untwisted.

Base doesn't move more than 1" (2.5 cm) side-to-side and front-to-back at the belt path.




Ensure tightness indicator is **GREEN** after each use. If it is not, reinstall base.

Base Installation with Vehicle Seat Belt Safety Check



Recline angle is correct. Check the level angle indicator on base to ensure the bubble is still within the lines. NO partial bubble allowed.



ALWAYS check the Recline Position Indicator on the base and adjust the recline bubble to be between the designated range indicated for the infant insert use.






Make sure the load leg is secured and contacts the vehicle floor. Check that the load leg angle indicator is **GREEN**. Ensure good contact between load leg foot and floor. Always store the load leg under the base when not in use.

ALL STEPS MUST BE COMPLETE.
If not, return to page 34 and start over.



Base Installation with Vehicle Seat Belt




UNINSTALLING BASE AND STORING LOAD LEG

- 1 Unbuckle seat belt. Open lock-off and remove seat belt.
- 2 Push load leg extension release button on back of load leg and bring foot up until it locks into place.
- 3 Bring load leg back into base until it clicks into secure/stowed position.

Carrier Installation with Vehicle Seat Belt



Carrier-only Installation can only be performed using the vehicle seat belt.
There is only 1 method of carrier-only installation.




LAP/SHOULDER EU ROUTING METHOD

Installation with both the lap and shoulder belt.




Carrier Installation with Vehicle Seat Belt

1



2



LEVELING THE CARRIER

- 1 Place the carrier rear-facing on the vehicle seat.
- 2 The **RED** line on the carrier must be level to the vehicle floor.





For a more stable installation, a rolled towel may be used.

Carrier Installation with Vehicle Seat Belt Lap/Shoulder Belt EU Routing Method



If you are having difficulty routing the shoulder belt behind the Aria carrier, contact Customer Service 1 (844) 823-3132, see page 50



- 1 Route the lap portion of the seat belt through both lap belt guides on the carrier, and buckle the seat belt.
- 2 Route belt around the seat back through the rear belt guide.

NOTE: Be careful not to pull too much of the Vehicle Shoulder Belt out of the Vehicle Retractor so it does not lock. If it locks, you will have to start over.




Carrier Installation with Vehicle Seat Belt Lap/Shoulder Belt EU Routing Method

- 3 Lock vehicle seat belt.
- 4 Push the carrier into the vehicle seat bight (crease of the seat) and gently apply pressure from behind the carrier into the vehicle seat back. At the same time, pull on the shoulder portion of the vehicle belt closest to the buckle and hold tightly.




NOTE: Be mindful of canopy.

- 5 Feed excess webbing into the vehicle retractor.
- 6 Rotate carry handle to mandatory (5th) rebound position or (4th) carry position when in vehicle.

NOTE: Check that the carrier is still properly leveled.



Carrier Installation with Vehicle Seat Belt Lap/Shoulder Belt EU Routing Method





**REVIEW SAFETY CHECK
ON PAGE 54.**

All steps must be achieved.



Carrier Installation with Lap Seat Belt



Aircraft Installation



- 1 Route the lap belt through both guides on the carrier, and buckle the seat belt.
- 2 Push the carrier into the aircraft seat bight (crease of the seat) and gently apply pressure from behind the carrier into the vehicle seat back. At the same time, pull on the loose portion of the lap belt closet to the buckle.

NOTE: Be mindful of canopy

Carrier Installation with Lap Seat Belt Aircraft Installation



- 3** Rotate carry handle to mandatory (5th) rebound position or (4th) carry position when in vehicle

NOTE: Check that the carrier is still properly leveled. Never use the AIRCRAFT SEATBELT PATH in a car. Always use the base or Lap/Shoulder EU routing method.

**REVIEW SAFETY CHECK
ON PAGE 54.**

All steps must be achieved.



Carrier Installation with Vehicle Seat Belt

Aircraft Installation



THIS CHILD SEAT IS CERTIFIED FOR AIRCRAFT USE WHEN USED WITHOUT A BASE.

UPPABABY AND THE FAA RECOMMEND THAT A CHILD WEIGHING UP TO 40 LBS (18 KG) USE A CERTIFIED HARNESS CHILD SEAT WHILE TRAVELING ON AN AIRCRAFT. CONTACT THE AIRLINE ABOUT THEIR POLICY PRIOR TO TRAVELING.

AIRCRAFT INSTALLATION

When installing this child restraint on an airplane, install with the **AIRCRAFT INSTALLATION METHOD** (Page 52).


NOTE: Make sure that the aircraft buckle does not interfere with the belt guides on the infant carrier.

WARNING: DO NOT use base with aircraft installation. Only the carrier is certified for aircraft use. Inflatable seat belts are not compatible with this child restraint.

SAFETY REMINDERS AND TIPS


- Notify the airline ahead of time that you'll be traveling with a child restraint and ask about their specific policies for using a child restraint system on board their aircraft.
- Install this carrier in a window seat to avoid blocking the aisle.
- Ask for a seat belt extender if the lap belt is too short.
- Use only on a forward-facing aircraft seat.
- DO NOT use this restraint if a secure installation cannot be achieved.
- Mandatory Carry handle use positions, must be in either the (5th) rebound position or (4th) carry position (child's foot end) for use in aircraft as long as it doesn't interfere with the back of the seat in front of the carrier.

Carrier Installation with Vehicle Seat Belt Safety Check



Carrier doesn't move more than 1" (2.5 cm) side-to-side and more than 1" (2.5 cm) front-to-back at the belt path. Have questions contact customer service 1 (844) 823-3132

Vehicle belt is secure and untwisted.



Angle is correct when The **RED** line on the carrier is level with the vehicle floor.

Seating position is permitted by both UPPAbaby and your vehicle manufacturer for use with the type of Vehicle Seat Belt.



NOTE: Mandatory Carry handle use positions, must be in either the (5th) rebound position or (4th) carry position when the car seat is in the vehicle.

General Use – Infant Insert

The infant insert is designed to optimize fit and body positioning for smaller infants. We recommend you use the infant insert starting at 4 lbs (1.8 kg) and up to approximately 4 months.


The infant insert is made up of two parts:

Preemie cushion **A**

Must be used in combination with the Back Positioning Insert. Recommended for use starting at 4 lbs (1.8 kg) and up to approximately 9 lbs (4.1 kg). Remove once infant reaches approximately 9 lbs (4.1 kg).

Back Positioning Insert **B**


Can be used alone or in combination with Preemie Cushion. Recommended for use starting at 4 lbs (1.8 kg) and up to approximately 4 months.



NOTE: Prior to installation, locate the fastener tabs on both sides of the headrest.

Installing infant insert

- 1 Find the fastener tabs within the inside of the headrest located on the upper left and right portion of the headrest.
- 2 With your **Back Positioning Insert**, tuck the fastener tabs under the headrest fabric and press to secure.
- 3 With your **Preemie Cushion**, secure cushion around the buckle to ensure a proper fit.



General Use – Infant Insert

INFANT INSERT USAGE WITH PREMIE CUSHION **A** AND BACK POSITION INSERT **B**


To ensure a better fit for smaller infants, use the 2-piece infant insert (included) for infants between 4 lbs (1.8 kg) and approximately 9 lbs (4.1 kg). This infant insert was designed to optimize fit and body positioning for your child.

NOTE: Continue to use the 2-piece infant insert until all criteria is met below:

- Harness straps are at or slightly below shoulders **1**.
- **NOTE:** Harness pads are optional. They must be removed when securing a preemie.
- Chest clip is at armpit level **2**.
- Child is not slouching and has good head and neck control.
- Crotch buckle rests securely against the child with no gaps and child is not sitting on top of the buckle.
- Harness can be properly tightened. Perform the pinch test to ensure proper fit.


NOTE: Once the infant reaches approximately 9 lbs (4.1 kg), the lower Premie Cushion can be removed and the Back Positioning Insert can continue to be used alone until approximately 4 months.

General Use – Infant Insert



HARNESS SHOULD BE SNUG.

Pinch harness webbing at child's shoulders. If you can pinch webbing, the harness is too loose and should be tightened.




ALWAYS check the Recline Position Indicator on the base and adjust the recline bubble to be between the designated range indicated for the infant insert use.

When using with the Aria base, align the bubble level toward the vehicle seat back within the approved range.

General Use – SIP Carriage and Harness Positioning

This child restraint has an adjustable head restraint and no-rethread harness system that is easy to adjust to properly secure the child.




1 Adjust the head restraint by pulling on the adjuster tab and sliding the head restraint up or down.

2 The Harness should be at the shoulders or slightly below.

NOTE: Minimum 1" (2.5 cm) gap between the child's head and top of headrest **A**. Harness should be at the shoulders or 1-2 positions below **B**.

WARNING: DO NOT place rolled towels or small blankets around head or SIP carriage. NEVER use non-regulated products with this child restraint, unless approved by UPPAbaby.



General Use – Securing Your Child





- 1 Loosen the harness by pressing on the harness adjuster release button and pulling out the shoulder straps toward the front of the carrier.
- 2 Open the retainer clip, unbuckle the harness, and tuck harness straps into belt guides to hold harness open.
- 3 Place infant in child restraint making sure their body is making full contact with the seating surface. Place harness over child and insert buckle tongues into the buckle until a “click” is heard. Pull up on the buckle tongues to make sure they are locked.

NEVER use non-regulated products with this child restraint, unless approved by UPPAbaby.

General Use – Securing Your Child




- 4 Pull up on the harness to remove excess slack around the child's legs.
- 5 Pull the harness adjuster strap to snugly adjust the harness straps around your child.
- 6 Close retainer clip and position at armpit level. Make sure the shoulder pads don't interfere with positioning the chest clip.



HARNESS SHOULD BE SNUG.

Pinch harness webbing at child's shoulders. If you can pinch webbing, the harness is too loose and should be tightened.

General Use – Attaching Carrier to Base




- 1 Place carrier on base until a click is heard.
- 2 Check for a secure connection by pulling up on carry handle.



NOTE: Mandatory Carry handle use positions, must be in either the (5th) rebound position or (4th) carry position when the car seat is in the vehicle.

General Use – Removing Carrier from Base

- 1 Pull and hold carrier release button on back of the carrier.
- 2 Lift carrier off base.



General Use – Using Canopy

Hide-away canopy easily adjusts to one of two (2) positions.

TO EXTEND CANOPY


Slowly pull forward on main canopy frame until resting in desired position.

TO STOW CANOPY

Gently push upward on main canopy frame allowing the center support and canopy fabric to guide into the storage compartment in carrier.



- 1 For additional coverage, the extended sunshade easily folds out and hides away for extra sun protection and privacy.

NOTE: Canopy can be in full extension or storage position while in vehicle. Never remove the canopy while in vehicle.





General Use – Using Carry Handle

To adjust the carry handle position, squeeze both handle adjustment buttons and rotate forward or backward.



WARNING: NEVER hang toys and other objects from the carry handle when using in the vehicle. These products have not been tested by UPPAbaby and therefore are not approved for use with this child restraint.


General Use – Safety Check




- This child restraint is for rear-facing use only.
- The seat must be tightly installed in a forward-facing vehicle seat.
- Minimum 1" (2.5 cm) gap between the child's head and top of headrest **A**.
- Harness should be at the shoulders or 1-2 positions below **B**.
- Retainer clip must be at armpit level and harness straps should be snug **C**.
- The top of child's head should not be less than 1" (2.5 cm) from the top of the headrest when in its highest position.
- The child must weigh between 4 and 30 lbs (1.8 and 13.6 kg) and be no taller than 30" (76.2 cm).
- The back seat is the safest place for children aged 13 and under.
- **NEVER** use non-regulated products with this child restraint, unless approved by UPPAbaby.
- **NEVER** place in front of an active airbag.
- Install using lower anchor or the vehicle seat belt, not both.
- **DO NOT** secure an infant in the carrier with extra material, bulky clothing, or extra padding. Instead place a blanket over the harness after properly securing the child **D**.
- Mandatory Carry handle use positions, must be in either the (5th) rebound position or (4th) carry position when in use in a vehicle
- While in vehicle, the canopy can be fully extended or in storage compartment.
- Adjust base to the appropriate angle by using the angle indicator on the sides of the base or the level to ground line on the carrier.
- Always check the tightness indicator is **GREEN** after each use.
- Always secure an unoccupied child restraint; in a crash an unsecured infant car seat may injure occupants in your vehicle.

Stroller Compatibility – Fitting Carrier to Stroller Frame

Prior to fitting Aria carrier to stroller frame, engage brake on stroller and remove toddler seat from frame.



- 1 With carrier facing stroller handle and carrier handle in carry position, align carrier handle hubs with attachment posts on stroller.
- 2 Let carrier slide onto attachment posts. An audible click indicates proper attachment.
- 3 Lift up on car seat handle to check attachment.





NOTE: Rock stop position is not permitted while using the stroller.

Compatible with Vista V3, Vista V2, Vista 2015+, Cruz V3, Cruz V2, Cruz. Compatible with Ridge, Minu and Minu Duo strollers with use of adapters specific to each model.



Stroller Compatibility – Releasing Carrier from Stroller Frame

- 1 Engage and hold the stroller release button on the back of the carrier.
- 2 Lift the carrier off stroller frame.





Care and Maintenance – SIP Padding Removal

Following are fabric removal instructions for cleaning.




- 1 With SIP in the highest position, unbuckle retainer clip and harness. Remove harness pads.
- 2 Pull up and forward on SIP padding releasing SIP adjustment tab.
- 3 Pull SIP padding toward you and down from bottom and release from harness straps.

Care and Maintenance – Seat Padding Removal





- 1 Start with headrest in the highest position. Release buckle from cover. Push buckle through opening under padding.
- 2 Unsnap harness adjustment strap.
- 3 Remove back panel of fabric by releasing closure and pull fabric out from under the SIP.
- 4 Remove the 2 plastic tabs at side of carrier and 2 plastic tabs at front of carrier to release fabric at front. Loosen fabric padding at the side buckle path.

Care and Maintenance – Seat Padding Removal




- 5 Remove buckle and harness adjustment strap through opening releasing the fabric.
- 6 Move SIP to the lowest headrest position. Release fabric from canopy clip at top of seat.
- 7 Pull fabric forward to release from top of the seat.
- 8 Pull fabric over the headrest to release from the seat.

Care and Maintenance – Seat Padding Installation





- 1 With the SIP in the lowest position, lay seat pad over the carrier and over the headrest.
- 2 Clip fabric back in place at canopy clip at top of seat.
- 3 While the fastened flap at the seat back is still open, raise the SIP headrest to its maximum height. Pull the harness straps forward, then tuck the seat back fabric beneath the SIP back carriage and fasten it securely using the closure.

Care and Maintenance – Seat Padding Installation



- 4 Slip buckle up through opening in seat cover and buckle cover.
- 5 Thread the harness adjustment webbing through the fabric opening.
- 6 Finish by securing the fabric around the front edge of the seat. Continue to tuck fabric around the outside edges of the seat including around the vehicle belt guides and then tuck the 4 tabs under the seat padding to secure.
- 7 Snap harness adjustment.

Care and Maintenance – SIP Padding Installation



- 1 Secure SIP cover tightly around SIP ears feeding SIP adjustment tab through opening in fabric.
- 2 Replace harness straps in front of SIP back padding.
- 3 Insert lower part of SIP carriage into pocket on the back of SIP padding.

Care and Maintenance – Cleaning

Cleaning Fabrics

Fabrics include: seat pad, infant inserts, buckle pads, shoulder pad, seat padding, SIP padding, harness pads, and buckle cover.



Machine wash in warm water on gentle cycle with mild detergent. DO NOT bleach.



Tumble dry low.



DO NOT iron or dry clean.

Cleaning Harness Webbing and Canopy



Spot clean using warm water with mild detergent. DO NOT bleach.



Air dry completely before re-use or storage.

Cleaning Plastic



Spot clean using warm water with mild detergent.



Towel dry completely before re-use or storage.

Cleaning Buckle and Lower Anchor Connector Hardware - Buckle should fasten with a “click” if not, rinse under warm running water. DO NOT use detergents or lubricants.

Warranty

PRODUCT LIFETIME WARRANTY

Lifetime warranty applies to UPPAbaby car seats and the original owner, within the lifetime of the product. To receive your Product Lifetime Warranty, you **MUST** provide a valid purchase receipt from an authorized UPPAbaby retailer. The lifetime of the product is up to 7 years from date of manufacture.

Your UPPAbaby product is warranted to be free from manufacturing defects for a period of 7 years from the date of manufacture under normal use and in compliance with the operating instructions.

This warranty is not transferable and extends only to the original retail purchaser and is only valid when supplied with proof of purchase from an authorized retailer. Proof of purchase must be retained for this warranty.

The warranty is valid only in the original country of purchase. This warranty is subject to the conditions set forth by country in which the items were purchased. Conditions may vary. UPPAbaby will not ship replacement or repair parts outside the country of purchase.

UPPAbaby will provide replacement parts or conduct repairs as determined fitting by the company. UPPAbaby reserves the right to exchange item with a replacement part. Some parts may be replaced with newer model parts as the item is improved over time.

Warranty

This warranty does not cover:

- Defects caused by misuse or poor maintenance. (Please refer to the product instruction booklet for guidance on item use and maintenance).
- Damage caused by improper installation of UPPAbaby parts and/or accessories. (Please refer to product instruction booklet for guidance on item assembly and use).
- Damage caused by corrosion mold or rust due to poor maintenance, service or storage.
- Damage resulting from normal wear and tear.
- Damage or degradation caused by the sun, sweat, detergents, damp storage conditions or frequent washings.
- Repairs or modifications carried out by a third party.
- Product purchased from an unauthorized retailer. (Approved retailers are listed on our website uppababy.com).
- Second owners and users other than the registrant.
- Damage resulting from airline shipping and handling.
- Products Involved in an accident.

UPPAbaby reserves the right to determine if warranty terms and conditions have been met.

For warranty service: In the US* and CA please contact UPPAbaby customer experience (844) 823-3132 and visit uppababy.com/support to send an email.

*Within the US, warranty conditions may differ from state to state.

Outside of the US and CA please contact your local distributor. Distributor information can be found at uppababy.com/global-distributors.



USA | UPPAbaby, 276 Weymouth Street, Rockland, MA 02370

uppababy.com | 1.844.823.3132

Model 1002-ARI-US

All rights reserved. © 2024 UPPAbaby. UPPAbaby and all associated logos are trademarks. All product specifications are correct at time of print. UPPAbaby reserves the right to change anything at any time without prior notice. Color representation is as close as print processes allow. Not all colors available at all retailers. UbMAN226-V10